

**CLEANING
STEAM LINE**



COMBY
professional



Comital-Sami

COMBY

professional



accessories

STANDARD 3000 4000 9000



DATI TECNICI	TECHNICAL DATA	CARACTÉRISTIQUES TECHNIQUES	DATOS TÉCNICOS	COMBY 3000	COMBY 4000
Ricarica continua	Continuous refilling	Recharge continue	Recarga continua		
Pressione di lavoro	Operating pressure	Pression d'exercice	Presión de operación	600 kPa (6 Bar)	800 kPa (8 Bar)
Potenza caldaia	Boiler power	Puissance chaudière	Potencia de caldera	2200 W	3400 W
Temperatura max	Temperature max	Température max	Temperatura máxima	160 °C	178 °C
Alimentazione elettrica	Electric power supply	Alimentation électrique	Alimentación eléctrica	230 V - 50 Hz	230 V - 50/60 Hz
Produzione vapore (acqua/ora)	Steam generation (water/hour)	Production vapeur (eau/heure)	Producción de vapor (agua/hora)	4 kg H ₂ O/h	5,5 kg H ₂ O/h
Capacità caldaia	Boiler capacity	Capacité chaudière	Capacidad de caldera	1,5 l	3 l
Dimensioni	Dimensions	Dimensions	Dimensiones	750x345x620 mm	750x380x700 mm
Serbatoio ricarica	Refill tank	Réservoir de recharge	Depósito de recarga	5 l	5 l
Peso	Weight	Poids	Peso	32 kg	38 kg
Serbatoio detergente	Detergent tank	Réservoir de détergent	Depósito de detergente	5 l	5 l
Contenitore recupero	Vacuum bucket	Bac de récupération	Recipiente de recuperación	7 l	7 l
Potenza max	Max power	Puissance max	Potencia de trabajo	3400 W	3500 W
Potenza aspirazione	Vacuum power	Puissance moteur	Potencia del motor	1200 W	1200 W

Commital-Sami

COMBY

professionali

G CLEANING
STEAM LINE

9000



4000

3000

accessories

OPTIONAL 3000 4000 9000



DATI TECNICI	TECHNICAL DATA	CARACTÉRISTIQUES TECHNIQUES	DATOS TÉCNICOS	COMBY 9000
Ricarica continua	Continuous refilling	Recharge continue	Recarga continua	
Pressione di lavoro	Operating pressure	Pression d'exercice	Presión de operación	800 kPa (8 Bar)
Potenza caldaia	Boiler power	Puissance chaudière	Potencia de caldera	9000 W
Temperatura max	Temperature max	Température max	Temperatura máxima	178 °C
Alimentazione elettrica	Electric power supply	Alimentation électrique	Alimentación eléctrica	230 V - 50/60 Hz
Produzione vapore (acqua/ora)	Steam generation (water/hour)	Production vapeur (eau/heure)	Producción de vapor (agua/hora)	15 kg H ₂ O/h
Capacità caldaia	Boiler capacity	Capacité chaudière	Capacidad de caldera	3,8 l
Dimensioni	Dimensions	Dimensions	Dimensiones	750x380x700 mm
Serbatoio ricarica	Refill tank	Réservoir de recharge	Depósito de recarga	15 l
Peso	Weight	Poids	Peso	47 kg
Serbatoio detergente	Detergent tank	Réservoir de détergent	Depósito de detergente	5 l
Contenitore recupero	Vacuum bucket	Bac de récupération	Recipiente de recuperación	7 l
Potenza max	Max power	Puissance max	Potencia de trabajo	10400 W
Potenza aspirazione	Vacuum power	Puissance moteur	Potencia del motor	1400 W

Commital-Sami

COMMITAL SAMI Spa

Via Fosse, 9 · I 36063 Marostica (Vicenza) Italy

Tel. +39.0445.851420 · Fax +39.0424.475121

www.committal-sami.it · info@commital-sami.it